

HIMAWARI 8/9 gridded full-disk (FD) data Version 02 (V20190123) release note

HIGUCHI, Atsushi, TAKENAKA, Hideaki, and TOYOSHIMA, Koichi:
Center for Environmental Remote Sensing (CEReS), Chiba University, Japan
(Last update: 08 September 2020)

List of Contents

1. Introduction
 2. Highlights in Version 02 (V20190123)
 - 2.1. Improvements for geo-correction accuracy
 - 2.2. 4km data release
 3. Gridded data specifications
 - 3.1. Data server (anonymous ftp server) and sub-directories rule
 - 3.2. Gridded data specification and the relation between CEReS released gridded data and JMA official HIMAWARI 8/9 AHI's bands
 - 3.3. File naming rules
 - 3.3.1. EXT (0.005 Degree; Approximately 500m spatial resolution at Nadir)
 - 3.3.2. VIS (0.01 Degree; Approximately 1km spatial resolution at Nadir)
 - 3.3.3. SIR (0.02 Degree; Approximately 2km spatial resolution at Nadir)
 - 3.3.4. TIR (0.02 Degree; Approximately 2km spatial resolution at Nadir)
 - 3.3.5. 4KM (0.04 Degree) [New!]
 - 3.4. Convert from raw digital number to physical variables, such as Tbb, spectral reflectance
 - 3.4.1. Convert from raw digital number to physical variables, such as Tbb, spectral reflectance
 - 3.4.2. Updating HIMAWARI-8 AHI Albedo Conversion Look Up Tables to Reflect New Calibration Coefficients (EXT, VIS, SIR) [New!]
 - 3.4.3. Inter-calibration activities (GSICS)
 4. About Citation
 - 4.1. About the treatments of the quasi-real-time dataset
- Acknowledgments

1. Introduction

CEReS released gridded-processed (latitude-longitude coordinated with geo-correction) Version 02 (V20190123) dataset of HIMAWARI 8/9 Advanced Himawari Imager (AHI) Full-Disk (FD) mode. Highlights of updated Version 02 are as follows;

2. Highlights in Version 02 (V20190123)

In Version 02 (V20190123) gridded dataset, we apply the technologies for the solar radiation product “AMATERASS” into a gridded dataset. Specifically, Version 02 improves geo-correction accuracy and adds 4km products such as physical variables and geometric information.

2.1. Improvements for geo-correction accuracy

Version 02 slightly improves the accuracy of geo-correction compared with Version 01 (V20151105). Users feel the benefit of using Version 02, particularly EXT utilization (0.005 Degree) during the daytime. On the other hand, Version 02’s geo-correction accuracy during the nighttime is the same as Version 01.

2.2. 4km data release

We add the 4km datasets, such as already converted physical variables and solar-sensor zenith and azimuth angles geometric information (see section 3.3.5).

3. Gridded data specifications

3.1. Data server (anonymous ftp server) and sub-directories rule

In the same manner as Version 01, users can get data files to access the anonymous ftp server (<ftp://hmwr829gr.cr.chiba-u.ac.jp/>). After anonymous login, please change directory; `gridded/FD/V20190123/`. Directly, users can access `ftp://hmwr829gr.cr.chiba-u.ac.jp/gridded/FD/V20190123/`. The server automatically generates directories and sub-directories as below rules.

YYYYMM YYYY: Year (4 digits). e.g., the Year of 2015 --> 2015 **MM**: Month (always 2 digits). e.g., August --> 08. Each YYYYMM directory has five sub-directories as below.

EXT VIS SIR TIR 4KM

Gridded data specifications stored in each sub-directory will describe in 3.3.3. Gridded data specifications.

3.2. Gridded data specification and the relation between CEReS released gridded data and JMA official HIMAWARI 8/9 AHI's bands

Our gridded data has different bands naming rule with JMA official Himawari 8/9 bands names. Tables 1 and 2 show the relation between our gridded data and JMA's Himawari 8/9 bands, and the common specifications for EXT, VIS, SIR, and TIR.

Table 1: Relation between CEReS gridded data and JMA's Himawari 8/9 AHI bands.

CEReS gridded		JMA AHI bands	Pixel x Line	Gridded spatial resolution
EXT	01	Band 03 (0.64 μ m)	24000 x 24000	0.005 Degree
VIS	01	Band 01 (0.47 μ m)	12000 x 12000	0.01 Degree
	02	Band 02 (0.51 μ m)		
	03	Band 04 (0.86 μ m)		
SIR	01	Band 05 (1.6 μ m)	6000 x 6000	0.02 Degree
	02	Band 06 (2.3 μ m)		
TIR	01	Band 13 (10.4 μ m)	6000 x 6000	0.02 Degree
	02	Band 14 (11.2 μ m)		
	03	Band 15 (12.4 μ m)		
	04	Band 16 (13.3 μ m)		
	05	Band 07 (3.9 μ m)		
	06	Band 08 (6.2 μ m)		
	07	Band 09 (6.9 μ m)		
	08	Band 10 (7.3 μ m)		
	09	Band 11 (8.6 μ m)		
	10	Band 12 9.6 μ m)		

Table 2: The common specifications of gridded dataset for EXT, VIS, SIR, and TIR.

Covered area:	85E – 205E (155W), 60N – 60S
Data type	2 byte “unsigned short” binary data without any header and footer information, with “big endian” byte order.
Data writing orders	West to East (left to right) and North to South (up to down)
Stored data is:	Himawari Standard (HS) data themselves (CCT count like). Note that non-data pixels are filled by the value of 65535 as the exception.

3.3. File naming rules

File name specifications are as follows; **YYYYMMDDHHMN.XXX.ZZ.fld.geoss.bz2**

YYYY: Year (4 digits), e.g., Year of 2015 -> 2015.

MM: Month (always 2 digits), e.g., August -> 08.

DD: Day (always 2 digits), e.g., 12th -> 12.

HH: Hour (always 2 digits; Unit is UTC), e.g., 02 UTC -> 02.

MN: Minute (always 2 digits; Unit is UTC), e.g., 10 minutes -> 10.

Timestamp in the file name represents "observation start time (start time to scan)".

XXX: CEReS gridded data wavelength-divided list. i.e., ext, vis, sir, and tir.

Sub-directory names are all capital (EXT, VIS, SIR, and TIR). But in filenames are expressed as small letters.

ZZ: CEReS gridded band number as listed in Table 1 (always 2 digits). fld: FD version.

geoss: no meaning. Simply CEReS geostationary gridded data's name rule.

3.3.1. EXT (0.005 Degree; 500m at Nadir)

Table 3 shows EXT (0.005 Degree, 500m) specifications and file naming rule.

Table 3: EXT gridded data specifications and file naming rule

CEReS gridded		JMA AHI band	Pixel x Line	Gridded spatial resolution
EXT	01	Band 03 (0.64 μ m)	24000 x 24000	0.005 Degree (500 m at Nadir)
<p>File Name : YYYYMMDDHHMN.ext.01.fld.geoss.bz2. YYYY: Year (4 digits), MM: Month (always 2 digits), DD: Day (always 2 digits), HH: Hour (always 2 digits; Unit is UTC), MN: Minute (always 2 digits; Unit is UTC), ext: CEReS grided data 'ext' represented, 01: CEReS gridded data band number (01 only for EXT), geoss: no meaning, bz2: bzip2 compressed file.</p>				
<p>Only EXT has static information for geo-correction. Log files YYYYMMDDHHMN.ext.(coff or loff).fld.txt.bz2 are exist. Normally do not need to see these files.</p>				

3.3.2. VIS (0.01 Degree; 1km at Nadir)

Table 4 shows VIS (0.01 Degree, 1km) specifications and file naming rule.

Table 4: VIS gridded data specifications and file naming rule

CEReS gridded		JMA AHI bands	Pixel x Line	Gridded spatial resolution
VIS	01	Band 01 (0.47 μ m)	12000 x 12000	0.01 Degree (1km at Nadir)
	02	Band 02 (0.51 μ m)		
	03	Band 04 (0.86 μ m)		
File Name : YYYYMMDDHHMN.vis.ZZ.fld.geoss.bz2. YYYY: Year (4 digits), MM: Month (always 2 digits), DD: Day (always 2 digits), HH: Hour (always 2 digits; Unit is UTC), MN: Minute (always 2 digits; Unit is UTC), vis: CEReS gridded data 'vis' represented, ZZ: CEReS gridded data VIS band number (thus 01, 02, and 03), geoss: no meaning, bz2: bzip2 compressed file.				

3.3.3. SIR (0.02 Degree; 2km at Nadir)

Table 5 shows SIR (0.02 Degree, 2km) specifications and file naming rule.

Table 5: SIR gridded data specifications and file naming rule

CEReS gridded		JMA AHI bands	Pixel x Line	Gridded spatial resolution
SIR	01	Band 05 (1.6 μ m)	6000 x 6000	0.02 Degree (2km at Nadir)
	02	Band 06 (2.3 μ m)		
File Name : YYYYMMDDHHMN.sir.ZZ.fld.geoss.bz2. YYYY: Year (4 digits), MM: Month (always 2 digits), DD: Day (always 2 digits), HH: Hour (always 2 digits; Unit is UTC), MN: Minute (always 2 digits; Unit is UTC), sir: CEReS gridded data 'sir' represented, ZZ: CEReS gridded data SIR band number (thus 01 and 02), geoss: no meaning, bz2: bzip2 compressed file.				

3.3.4. TIR (0.02 Degree; 2km at Nadir)

Table 6 shows TIR (0.02 Degree, 2km) specifications and file naming rule.

Table 6: TIR gridded data specifications and file naming rule

CEReS gridded		JMA AHI bands	Pixel x Line	Gridded spatial resolution
TIR	01	Band 13 (10.4 μ m)	6000 x 6000	0.02 Degree (2km 相当)
	02	Band 14 (11.2 μ m)		
	03	Band 15 (12.4 μ m)		
	04	Band 16 (13.3 μ m)		
	05	Band 07 (3.9 μ m)		

	06	Band 08 (6.2 μ m)		
	07	Band 09 (6.9 μ m)		
	08	Band 10 (7.3 μ m)		
	09	Band 11 (8.6 μ m)		
	10	Band 12 9.6 μ m)		

File Name : YYYYMMDDHHMN.tir.ZZ.fld.geoss.bz2.
 YYYY: Year (4 digits), MM: Month (always 2 digits), DD: Day (always 2 digits), HH: Hour (always 2 digits; Unit is UTC), MN: Minute (always 2 digits; Unit is UTC), tir: CEReS grided data 'tir' represented, ZZ: CEReS grided data TIR band number (thus from 01 to 10), geoss: no meaning, bz2: bzip2 compressed file.

3.3.5. 4KM (0.04 Degree) [New!]

4KM data is Version 02's new product. 4KM data stored in day's sub-directories such as; <ftp://hmwr829gr.cr.chiba-u.ac.jp/gridded/FD/V20190123/YYYYMM/4KM/YYYYMMDD/>. 4km data specifications and file naming rules are represented in Table7.

Table 7 : 4KM data specifications and file naming rule (a: common specification)

Pixel x Line, resolution	3000 x 3000, 0.04 Degree (4km at Nadir)
Covered area	85E – 205E (155W), 60N – 60S (same as the other dataset)
Data type	4 byte “float” binary data with “big endian” byte order.
Data writing orders	West to East (left to right) and North to South (up to down)
Stored data is:	Already converted to physical variables

(b: EXT, VIS, SIR, TIR physical variables converted dataset)

File name example	Physical Variable
YYYYMMDDHHMN.xxx.ZZ.rad.fld.4km.bin.bz2 (xxx: ext, vis, sir, tir; ZZ: CEReS grided data band number)	ext, vis, sir, tir irradiance (unit: $W m^{-2} sr^{-1} \mu m^{-1}$)
YYYYMMDDHHMN.xxx.ZZ.rfc.fld.4km.bin.bz2 (xxx: ext, vis, sir; ZZ: CEReS grided data number)	ext, vis, sir spectral reflectance (dimensionless)
YYYYMMDDHHMN.xxx.ZZ.rfy.fld.4km.bin.bz2 (xxx: ext, vis, sir; ZZ: CEReS grided data number)	ext, vis, sir spectral reflectance (%)
YYYYMMDDHHMN.tir.ZZ.tbb.fld.4km.bin.bz2 (ZZ: CEReS grided data number)	tir (only) brightness temperature (Tbb (K))

(c: geometries dataset)

Filename example	Physical Variables
YYYYMMDDHHMN.sun.azm.fld.4km.bin.bz2	Solar azimuth angle (Degree, South direction is zero, clockwise rotation)
YYYYMMDDHHMN.sun.zth.fld.4km.bin.bz2	Solar zenith angle (Degree)
YYYYMMDDHHMN.sat.azm.fld.4km.bin.bz2	Sensor azimuth angle (Degree, South direction is zero, clockwise rotation)
YYYYMMDDHHMN.sat.zth.fld.4km.bin.bz2	Sensor zenith angle (Degree)
YYYYMMDDHHMN.grd.time.mjd.hms.fld.4km.bin.bz2	Scanning time (Normalized 0 to 1, i.e., 12:00 UTC is 0.5)
YYYYMMDDHHMN.lat.fld.4km.bin.bz2	Latitude (Degree)
YYYYMMDDHHMN.lng.fld.4km.bin.bz2	Longitude (Degree)
YYYYMMDDHHMN.cap.flg.fld.bin.bz2 ^{*1}	Cloud flag (Daytime and over ocean only. More than 1 represents cloud)

*1: only cap.flg is consists of 2 byte unsigned short binary with big endian byte order.

3.4. Convert from raw digital number to physical variables, such as Tbb, spectral reflectance

Except for the 4km product, the conversion process will need. The conversion from raw digital data into physical variables, such as brightness temperature (Tbb for TIR), and spectral reflectance for visible, near-IR (EXT, VIS) and shortwave-IR (SIR) by the calibration tables of which produced by JMA, the users has to need data processing via programing.

3.4.1. Convert from raw digital number to physical variables, such as Tbb, spectral reflectance

We made sample programs (F90 and C) and calibration tables as a tarball of count2tbb_v102.tgz. The same tarball can download at;
<ftp://hmwr829gr.cr.chiba-u.ac.jp/gridded/FD/support/>

Version 102 sample programs are a bug-fix version of which overcomes exception handing. If you already have version 101 sample programs, please switch version 102. Also, PC-based OS such as Windows, Intel macOS, Linux (i386, x86_64), standard binary data reading order is little-endian. Thus, before processing our sample programs, the user needs to byte swapping process. In the case of bash, dd command can do such byte swap process as follows;

\$dd if=(input binary) of=(output binary) conv=swab

Such a byte swap does not need native 64bit environments such as Power PC, Intel Itanium (IA-64), SPARC, HP-UX, etc.

[Note] Even though 64bit OS in intel/AMD CPU, such as Linux x86_64, macOS, Windows 64bit, our sample programs for EXT (24000 pixels x 24000 lines) band data process as that;

- a) A band data splitting into two files as the Northern area and Southern area.
- b) Then C and F90 program convert CCT to reflectance for each splitting file.
- c) After conversion, merge two files into one. (please see the detail processes in shell scripts in the tarball) This process is mainly due to the limitation of malloc (memory allocation). Moreover, under the 32bit OS, due to 32bit OS (limitation of 32bit), it is impossible to generate a file more than 2 GB in its file size. If users try to analyze EXT data by 32bit OS, the user needs to treat EXT physical converted data as split files (e.g., Northern and Southern areas).

If you want to read more detail on reading gridded data, the below URL is maybe useful.
http://quicklooks.cr.chiba-u.ac.jp/~himawari_movie/rd_gridded.html

3.4.2. Updating HIMAWARI-8 AHI Albedo Conversion Look Up Tables to Reflect New Calibration Coefficients(EXT, VIS, SIR) [New!]

CEReS LUTs are based on the original calibration coefficients. Due to degradation, JMA's Meteorological Satellite Center (MSC) updates AHI calibration coefficients annually. Professor Tomoaki Miura of the University of Hawai'i created new LUTs to reflect these new calibration coefficients. If the user analyzes the long-term trend, it is better to apply these LUTs. Through Professor Miura's courtesy, we can release updated LUTs for EXT, VIS, and SIR bands Updated_LUT_20200308_zip.zip.

Useful reference : Update of Calibration Information Used to Correct Himawari-8 AHI Sensitivity Trend

(https://www.data.jma.go.jp/mscweb/en/oper/eventlog/Update_of_Calibration_Information_2020.pdf accessed on 03 September 2020) .

3.4.3. Inter-calibration activities (GSICS)

Global Space-based Inter-calibration System (GSICS) is one of the space components of the World Meteorological Organization (WMO). Its mission is to provide users with high-quality and inter-calibrated measurements from operational satellites. JMA MSC operationally has been providing information about inter-calibration results at Himawari

Calibration Portal:

https://www.data.jma.go.jp/mscweb/en/oper/calibration/calibration_portal.html

(accessed on 01 September 2020)

4. About Citation

Please cite two papers listed as below.

Geo-correction algorithm : Takenaka, H., T. Sakashita, A. Higuchi, T. Nakajima (2020):

Development of geolocation correction for geostationary satellite observation by phase only correlation method using visible channel, *Remote Sensing*, **12** (15), 2472

doi.org/10.3390/rs12152472.

Geo-correction accuracy validation : Yamamoto, Y., K. Ichii, A. Higuchi, H. Takenaka

(2020): Geolocation accuracy assessment of Himawari-8/AHI imagery for application to terrestrial monitoring, *Remote Sensing*, **12** (9), 1372 doi.org/10.3390/rs12091372.

Besides, please describe below sentence in Acknowledgements; "*Himawari 8/9 gridded data are distributed by the Center for Environmental Remote Sensing (CEReS), Chiba University, Japan.*" CEReS H8/9 gridded data is limited for non-commercial use. This data policy is the same as JMA's one for academic-data-releasement. We also prohibit the distribution of our gridded data to third parties, except among the research communities.

4.1. About the treatments of the quasi-real-time dataset

Due to the data policy of JMA, quasi-real-time data (in the definition of JMA, real-time data is within 24 hours data since now) cannot open without any restriction. Thus, in the CEReS ftp server, we control the access for quasi-real-time data by IP address. If the user wants to access quasi-real-time data for non-commercial use only, please send an e-mail with the accessed global IP address and its objective to below e-mail address.

request4himawaridata_AT_ceres.cr.chiba-u.ac.jp. We have no plan to change the configuration on the CEReS ftp server by user registration. We will do via IP based restriction only.

Acknowledgments

This activity is partly supported by the Virtual Laboratory (VL) project funded by the Ministry of Education, Culture, Sports, Science and Technology (MEXT), Japan, JST/CREST TEEDA, and the President leaderships of Chiba University. We thank Prof. HAMADA, Atsushi of Toyama University, who pointed out our sample programs bug and

contributed to the program improvements. Thanks, expand to Prof. MIURA Tomoaki of the University of Hawai'i created new LUTs to reflect these new calibration coefficients.